

ESSEX EQUIPMENT

MILLER
POWER BUGGIES



Operation Information for Counter and Sales personnel

Material in this manual is designed to provide you with information for safe customer operation of the Miller B 16 Concrete Buggy.

Basic Specifications

MILLER POWER BUGGIES	B-16
Engine	Honda™ GX390 (389 cc) Recoil or Electric Start
Payload	2,500 lb (1,134 kg)
Dimensions (L x H)	97 in x 50 in (246 cm x 127 cm)
Length (With Platform Up)	88.5 in (225 cm)
Dimensions (Width)	47 in (119 cm)
Wheelbase	40 in (102 cm)
Bucket Capacity	16 cu. ft.
Weight	Poly Bucket: 1,300 lb (590 kg) Steel Bucket: 1,450 lb (658 kg)
Lift Cylinder	2" Diameter
Dump/Return Speed Emph	5 Seconds
Top Speed	7 mph
Fuel Capacity	1.7 gal (6 L)

1. Solid 2" thick steel frame
2. Foam-filled tires are standard
3. Side-to-side and rear-to-front forklift pockets
4. Isolated Steering Column
5. Easy-squeeze speed control lever
6. Hydraulic dump
7. Enclosed ventilated engine shroud
8. Foot-operated dumping controls
9. Heavy-duty poly dump bucket
10. Powerful gasoline engines



DANGER

Operate this equipment only from the operator's platform and facing the front of the vehicle.

