


Hilti USA:
(866) 445-8827

Home > Products > Diamond Coring & Sawing > Diamond Coring > Diamond Coring Systems > DD 130
Diamond
Coring
System

DD 130 Rig Kit: Item No.: 03436357



Package quantity	1
Number of packages	1

Technical Data

Rated input	1900 W
Drilling range	15/32 in - 6 in
Nominal Current	15 A
Frequency	50/60 Hz
Protection class	Grounded (class I)
For Use With	HDM core bits, PCM core bits, HWC core bits, P-line core bits
A-weighted sound power level acc. EN 60745	100 dB (A)
A-weighted emission sound pressure level acc. EN 60745	89 dB (A)
Dimensions (L x W x H)	20.3 x 4.5 x 6.7 in
Weight	16.1 lb
Weight (motor and stand)	28.6 lb
Chuck Style	BI+
Wall accessibility	1-1/2 in
Corner accessibility	2-1/4 in
Coring height with water collection in place	430 mm
Number of Gears	3
Speed 1 No Load	780 rpm

Speed 2 No Load	1400 rpm
Speed 3 No Load	2600 rpm
Coring range gear 1 (dry) (Imperial)	4.8 in - 6.38 in
Coring range gear 1 (wet) (Imperial)	2.24 in - 5.98 in
Coring range gear 2 (dry) (Imperial)	2.64 in - 4.8 in
Coring range gear 2 (wet) (Imperial)	1.1 in - 2.05 in
Coring range gear 3 (dry) (Imperial)	0.63 in - 2.44 in
Coring range gear 3 (wet) (Imperial)	0.47 in - 0.98 in
Drilling range - dry	0.63 in - 6.38 in
Drilling range - wet hand held	0.63 in - 5.2 in
Drilling range - wet w/ stand	0.47 in - 5.98 in
Opt. drilling range - dry	0.63 in - 5.2 in
Opt. drilling range - wet hand held	0.63 in - 4.41 in
Opt. drilling range - wet w/ stand	16 mm - 132 mm
Lifetime Service No Cost Period	2 years

Related Products

DD-BI P2 Diamond core bit
 DD-BI P4 Diamond core bit
 DD-BI U4 Diamond Core Bits
 DD-BT PM-D Diamond core bit
 DD 100 / PMD Adaptor
 15/20 Amp Twist Lock Adapter

[Go back to previous page](#)

Hilti. Outperform. Outlast.

Hilti = registered trademark of Hilti Corp., LI-9494 Schaan, Principality of Liechtenstein
 © 2009-2010, Right of technical and programme changes reserved, S.E. & O.