



# SPECIFICATIONS

	EU1000iA2	EU2000iA / EU2000iA Companion†	EU3000iA	Handi EU3000i	EU6500iA
<b>Engine</b>	Honda GXH50	Honda GX100	Honda GX200	Honda GX160	Honda GX390
	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead cam, air-cooled	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled	Single cylinder, overhead valve, air-cooled
<b>Displacement</b>	50cc	98.5cc	196cc	163cc	389cc
<b>AC output</b>	120V 1000W max. (8.3A) 900W rated (7.5A)	120V 2000W max. (16.7A) 1600W rated (13.3A)	120V 3000W max. (25A) 2800W rated (23.3A)	120V 3000W max. (25A) 2600W rated (21.7A)	120/240V 6500W max. (54.1/27.1A) 5500W rated (45.8/22.9A)
<b>I/AVR AC output</b>	N/A	N/A	N/A	N/A	N/A
<b>Receptacles</b>	B	C / F, J†	C, F	C, F	C, F, H
<b>DC output</b>	12V, 96W (8A)	12V, 96W (8A)	12V, 144W (12A)	12V, 100W (8.3A)	N/A
<b>Starting system</b>	Recoil	Recoil	Recoil, electric	Recoil	Recoil, electric
<b>Fuel tank capacity</b>	0.6 gal.	1.1 gal. / .95gal.†	3.4 gal.	1.56 gal.	4.5 gal.
<b>Run time per tankful</b>	3.8 hrs. @ rated load, 8.3 hrs. @ 1/4 load	4hrs. @ rated load, 9.6 hrs. @ 1/4 load	7.2 hrs. @ rated load, 20.0 hrs. @ 1/4 load	3.6 hrs. @ rated load, 7.7 hrs. @ 1/4 load	4.7 hrs. @ rated load, 14.0 hrs. @ 1/4 load
<b>Dimensions (L x W x H)</b>	17.7" x 9.4" x 15.0"	20.1" x 11.4" x 16.7"	25.8" x 18.9" x 22.4"	24.5" x 14.9" x 19.3"	33.5" x 26.4" x 27.5"
<b>Noise level</b>	59 dB @ rated load 53 dB @ 1/4 load 86 LwA"†	59 dB @ rated load 53 dB @ 1/4 load 89 LwA"†	58 dB @ rated load 49 dB @ 1/4 load 90 LwA"†	65 dB @ rated load 57 dB @ 1/4 load 91 LwA"†	60 dB @ rated load 53 dB @ 1/4 load 91 LwA"†
<b>Dry weight</b>	29 lbs.	46.3 lbs. / 45.9 lbs.†	134 lbs.	78 lbs.	253 lbs.

# FEATURES

	EU1000iA2	EU2000iA / EU2000iA Companion†	EU3000iA	Handi EU3000i	EU6500iA
Honda OHV engine	•	•	•	•	•
Electric start/Remote start option					•
Oil Alert*	•	•	•	•	•
Auto Throttle*					
Eco-Throttle™ (load dependent operation)	•	•	•	•	•
Electronic ignition	•	•	•	•	•
Simultaneous AC/DC use	•	•	•	•	•
Circuit breakers	Electronic	Electronic	Electronic	Electronic	Electronic
Fuel gauge			•	•	•
•-Monitor					•
Wheel lid standard		OPT	OPT	•	•
I/AVR					
D/AVR					
CycloConverter™					
Inverter	•	•	•	•	•
One switch for engine/fuel valve on/off	•	•		•	
Full tubing frame for protection					
USDA-qualified spark arrester/muffler	•	•	•	•	•
Fully enclosed for quieter operation	•	•	•	•	•
120/240V selector switch					•
GFCI/neutral bond					
Residential warranty	2 Years	3 Years	3 Years	3 Years	3 Years
Commercial warranty	1 Year	3 Years	3 Years	3 Years	3 Years

† indicates a specification for EU2000iA Companion model only.  
 ††LWA is an international noise level measurement that uses a weighting factor to reflect noise "tonality" in addition to the sound power (dBA) level.

### Receptacle Key

RECEPTACLE	DESCRIPTION	PLUG #	RECEPTACLE	DESCRIPTION	PLUG #
B	15A 125V Duplex	5-15P	D	20A 125V GFCI Duplex	5-20P
C	20A 125V Duplex	5-15P or 5-20P	E	20A 125V Locking Plug	L5-20P