

ZG

ZG222/ZG222S ZG227/ZG327

SPECIFICATIONS

Specifications

Model		ZG222		ZG227	ZG327	
		ZG222-48S	ZG222-48	ZG227-54	ZG327P-60	
Engine	Model	Kubota KGZ770-E2-M3		Kubota KGZ770-E2-M2	Kubota KGZ770-E2-M1	
	Type	Gasoline, air-cooled V-Twin with heavy-duty canister air filter				
	Max. horsepower (Gross)	22HP@3600 rpm		27HP@3600 rpm		
	Total displacement	46.87 cu.in. (768 cc)				
	Starting system	Key switch				
Dimensions	Overall length	81.1 in. (2060 mm)	82.4 in. (2093 mm)		87.8 in. (2230 mm)	
	Overall width	w/ mower	61.0 in. (1550 mm)	61.1 in. (1552 mm)	67.3 in. (1710 mm)	75.2 in. (1911 mm)
		w/o mower		47.7 in. (1210 mm)		57.5 in. (1460 mm)
	Overall height	w/ ROPS upright		69.9 in. (1775 mm)		75.4 in. (1915 mm)
		w/ ROPS folded		51.9 in. (1320 mm)		61.2 in. (1555 mm)
Wheel base		51.0 in. (1295 mm)		55.5 in. (1410 mm)		
Tread	Front		33.9 in. (860 mm)		38.4 in. (975 mm)	
	Rear		36.6 in. (930 mm)		45.3 in. (1150 mm)	
Tire size	Front		13× 5.0-6 Pneumatic		15× 6.0-6 Semi-Pneumatic	
	Rear		23× 10.5-12		26 12.0-12	
Weight (w/ mower) (without fuel)		1098 lbs. (498 kg)	1177 lbs. (534 kg)	1199 lbs. (544 kg)	1473 lbs. (668 kg)	
Transmission system		2-HST w/ Gear reduction				
Speed control		2-hand lever				
Travel speed range	Forward	0-9.0 mph (0-14.5 km/h)		0-10.6 mph (0-17.0 km/h)		
	Reverse	0-5.0 mph (0-8.0 km/h)		0-5.3 mph (0-8.5 km/h)		
Brake type		Wet multi disks, foot operated				
PTO	Type	Shaft drive				
	Clutch type	Hydraulic independent PTO clutch with wet multi disks				
	PTO brake	Wet single disk				
Mower deck	Model	RCK48S-222Z	RCK48P-222Z	RCK54P-227Z	RCK60P-327Z	
	Mower lift system	Hydraulic				
	Mower deck type	Stamped deck	Pro commercial—Fabricated deck			
	Deck depth	5.0 in. (127 mm)	6.0 in. (152 mm)		6.5 in. (165 mm)	
	Belt type	Multi-Belt				
	Deck steel thickness	0.13 in. (3.4 mm)	0.17 in. (4.2 mm)/0.18 in. (4.6 mm)			
	Anti-scalp roller	Rigid				
	Cutting width of mower	48 in.		54 in.	60 in.	
	Number of blades	3 blades				
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments				
	Mounting system of mower	Parallel linkage				
	Blade tip speed (max.)	15800 FPM	17000 FPM		18100 FPM	
	Engine stop system		Key stop			
Fuel tank capacity		7.4 gals. (28 ltrs.)		12.9 gals. (49 ltrs.)		
Battery		12 Volts, UIL-9, 300CCA@0°F, 30 min. RC.				
Alternator capacity		13.4 Amps at 12 Volts				
Hour meter		Standard				
Fuel gauge		Electric				