



**CBA-4004-0MHB**

**Pump:** Belt drive triplex piston AR pump with ceramic plungers · Stainless-steel and brass unloader · Adjustable pressure · Forged brass manifold · Thermal relief valve · Water filter with clear sleeve for screen inspection

**Engine:** Performance-proven Honda OHV engine with low-oil protection

**Frame:** Light, corrosion resistance aluminum frame · 1-inch aluminum tube handles for easier pulling · Two-piece belt guard for quick access to belts · Pneumatic tires with tubes for longer life · Dual rubber isolators · Aluminum base plate and solid 7/8-inch diameter full-length threaded axle · Patented vibration isolation plate with four rubber isolators for reduced movement

**Component:** Dual cogged belt drive system for increased belt life

**Unit Includes:** Quick connect nozzles (0°, 15°, 25° and 40°) · 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors · Professional-grade insulated trigger gun with safety lock-off · 48-inch lance with rubber grip

**Specifications**

PSI	4000
GPM	3.4
Displacement/Engine	389cc Honda OHV

**Weights & Dimensions**

Net Weight	165 lbs.
Shipping Weight	215 lbs.
Length	47 in.
Width	27.5 in.
Height	28.5 in.