

# MORBARK® BEEVER™ M12R

## BENEFITS

- Powerful Hydra-Lift™ dual feed wheel compression system generating over 3,300 lb/ft of combined material pulling force
- New larger infeed opening with 60" wide x 31" high perimeter opening and 15" wide x 12" high throat opening
- New chambered air impeller system increases chip throwing velocity and reduces dust and material blowback out the infeed
- Ideal unit for: Utility line clearing, residential tree services, rental yards and municipalities. Also available in PTO and Track configurations.



**TOP FEED WHEEL**  
18" diameter top feed wheel with combination serrated teeth and knife bars



**DRIVE BELT COVER**  
Drive belt inspection cover provides ease of drive system maintenance



**HYDRA-LIFT™ SYSTEM**  
Hydra-Lift Compression System with spring assisted down pressure



**DISCHARGE**  
360° Manual Crank Swivel Discharge

## SPECIFICATIONS

Note: Specifications may vary with equipment options

06092010

### GENERAL

Chipping capacity ..... 12"  
Length ..... 15'  
Height ..... 8'5"  
Width ..... 5' 11"  
Gross weight ..... 5,500 lbs.  
Suspension ..... 6,000 lb. torsion  
Infeed Opening ..... 60" wide x 31" high  
Throat Opening ..... 15" wide x 12" high  
Drum ..... 14 1/2" wide x 21 3/8" diameter  
Engines ..... CAT, Cummins, or Kubota  
Horsepower ..... 84 HP - 115 HP  
Fuel capacity ..... 24 1/2 gallons  
Hydraulic oil capacity ..... 17 gallons  
Frame ..... 2" x 4" tubular  
Tires ..... (2) LT245/75R x 16"  
Hitch ..... 2 1/2" Lunet

### EQUIPMENT HIGHLIGHTS

Increased feeding efficiency - Direct driven dual feed wheel system with serrated teeth and knife bar combination and end cap ripper teeth allow positive material feeding and reduced material wrapping around the feed wheel shaft  
Hydra-Lift top feed wheel compression system with spring assisted down pressure provides over 1,500 lbs. of material crushing power  
Reversing automatic feed system  
2-pocket, staggered knife cutting system allows 1.43 cuts per revolution  
360° Manual crank swivel discharge with spring loaded adjustable chip deflector  
Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high gloss finish, built in UV protection, chip and chemical resistance and corrosion protection

### ADDITIONAL FEATURES

Bottom feed wheel clean-out door  
Telescoping drawbar with (2) 12" horizontal extensions  
8D, 1400CCA battery  
Dual safety pull cables located within infeed  
Hydraulic tank inspection cover

### OPTIONS

Winch package  
Aluminum diamond plate fenders  
Radiator brush guard  
Folding infeed tray  
Custom paint and logo packages  
Knife saver tool  
Engine E-stop  
Material pushing tool



800-831-0042 989-866-2381  
[www.morbark.com](http://www.morbark.com)