

An Overview of the Paslode Angled Finish Nailer

Description

The Paslode Angled Finish nailer is a self-contained, fully portable nailer that uses liquid hydrocarbon fuel to power a unique linear drive internal combustion motor.

In order for you to fully understand the information contained in this manual, you need a basic understanding of the Paslode Angled Finish nailer. As you can see in the illustration below, the Paslode Finish nailer is made up of three major areas: handle, motor, and magazine.

As you examine the Paslode Angled Finish nailer, become familiar with the three major areas and the various components located in each of them.

The **Handle** contains the fuel cell, indicator light, and the trigger.

The **Motor** contains the cover and filter, the motor housing, the nose, and the work contacting element.

The **Magazine** contains the components to load and control the fastener and the battery for the Paslode Angled Finish nailer.

Specifications

Dimensions: Weight-with battery 4 lbs 14oz.
 Height 11-1/2 inches
 Length 10-3/4 inches
 Magazine Angled
 (use Paslode angled fasteners only.)

Cycle Rate: Intermittent Operation – 2 to 3 nails per second
 Continuous Operation – 500 nails per hour

NOTE: Exceeding these cycle rates could cause the tool to overheat, resulting in loss of performance or damage to tool components.

By using the Paslode Angled Finish nailer at its recommended cycle rate, you will be able to drive several thousand nails in a typical workday.

Fasteners: 16 gauge, angled F-16 Series, Chisel Point

Magazine Capacity: 2 nail strips, or 100 fasteners

Battery : 6 volts DC - Provides enough energy to drive approximately 4000 fasteners on a full charge.

Fuel Cell: Liquid hydrocarbon - Provides enough fuel to drive approximately 1200 fasteners.

