



The **F**irst Name in Turf Renovation™

## MATAWAY® OVERSEEDER



**High-productivity overseeder dethatches  
and overseeds in one pass.**

Specifications, while correct at the time of printing, may change without notice.

Ryan® is a registered trademark of Commercial Grounds Care, Inc.

© 2006 CGC, Inc. • One Bob Cat Lane • Johnson Creek, WI 53038 • [www.ryanturf.com](http://www.ryanturf.com)

# MATAWAY® OVERSEEDER

## POWER

Engine .....4-cycle OHV Kohler® Command Pro; cast-iron bore; recoil starter; dual element air cleaner  
Horsepower (@ 3,600 rpm) .....11 (8 kW)  
Displacement .....24.3 cu. in. (398 cc)  
Oil Capacity .....2 qt. (1.9 L)

## UNIT

Clutch .....Spring-loaded belt tightener  
Primary Drive.....4L-section V-belt to front wheels by gear box and sealed roller chain;  
triple 3V-section V-belts from engine to reel  
Lubrication .....Oil splash in gear case; pressure grease fitting elsewhere  
Cutting Depth .....Adjustable to any desired depth up to 1.5 in. (38 mm)  
Slicing Width .....19 in. (483 mm)  
Front Tires .....Two 10.4 x 4.10-4, 2-ply, pneumatic; knob tread  
Rear Tires .....Two 10.25 x 4.10-4, 2-ply, pneumatic; sawtooth tread

## DIMENSIONS

Weight.....462 lbs. (210 kg) with hopper/reel  
Width.....35.5 in. (0.9 m)  
Length .....54 in. (1.4 m)  
Height .....43 in. (1.1 m)

## HOPPER

Capacity .....0.83 cu. ft. (0.02 cu. m)  
Configuration .....Rectangular top with side tapering down to feed rotor bar  
Size.....8.5 in. W x 18.5 in. L x 13 in. H (216 x 470 x 330 mm)  
Seed Density .....Fully adjustable for all types of common grass seed

## ROTOR BAR AND METERING SYSTEM

Metering System .....Stainless steel plates with triangular-shaped holes slide over  
each other to create a variable opening  
Rotor Bar .....Neoprene rubber  
Seed Flow Control .....Rotor bar stop; gate shutoff  
Rotor Bar Drive .....Direct drive powered by frontwheel-drive unit  
Rotor Bar Operation .....Engages in lowered-reel position only  
Seed Gate Operation .....Automatically shuts off when unit is raised  
Maintenance .....Rotor bar and metering device remove easily for servicing

## LOWER SEED DELIVERY SYSTEM

Seed Tubes .....Clear plastic  
Seed Outlets .....10 at 2 in. (51 mm) spacing  
Discs .....10 high-carbon, heat-treated disc blades with scrapers  
Detachable .....4 removable pins attach disc assembly to Mataway  
Slicing Reel .....Hardened, 1 in. (25 mm) hex shaft  
Fixed Blades .....10 8-pt., high-carbon, heat-treated blades designed for slicing and longer wear life;  
spaced 2 in. (51 mm) centers

## OPTIONAL VERTICAL SLICER/DETHATCHER

Flail Blade Type .....1/8 in. (3 mm) at 1 in. (25 mm) spacing  
Fixed Blade Type .....1/32 in. (1 mm) at 1/2 in. (13 mm) spacing; 1/32 in. (1 mm) at 1 in. (25 mm) spacing;  
1/16 in. (2 mm) at 1 in. (25 mm) spacing; 1/16 in. (2 mm) at 1 1/2 in. (38 mm) spacing

Specifications, while correct at the time of printing, may change without notice.

Ryan® is a registered trademark of Commercial Grounds Care, Inc.

© 2006 CGC, Inc. • One Bob Cat Lane • Johnson Creek, WI 53038 • www.ryanturf.com