

| | | |
|--|---|---|
| MODEL | | 5725 |
| PERFORMANCE | Gross Engine Horsepower PTO HP @ Rated Engine RPM (Gear) KW PTO HP @ Rated Engine RPM (Hydro) KW | 22.9 @ 2,800 (17.1) 19.0 @ 2,800 (14.2) 18.4 @ 2,800 (13.7) |
| ENGINE | Number of Cylinders/Aspiration Type of Cooling/Fuel Total Displacement; in. ³ (Liters) | 3 Natural Liquid / Diesel 68.5 (1.1L) |
| GEAR TRANSMISSIONS | Type - Standard Type - Optional Type of Gears No. of Speeds F/R No. of Ranges Creeper | Mechanical NA Collar Shift 6 X 2 2 - NA |
| HYDROSTATIC TRANSMISSIONS | Type Type of Range Forward Speeds; mph (kph) No. of Ranges | Hydrostatic Sliding Gear Infinite 0 - 13.4 (0 - 21.6) 2 |
| POWER TAKE-OFF (PTO) | Type Speeds; (rpm @ rated engine speed) Rear/Mid PTO Output Locations (Rear/Mid) | Trans Driven / Ind. Hydro 540/2000 Rear / Mid Std |
| 3-POINT HITCH | ASAE Category Control Type of Draft Sensing Stabilizers Lift Capacity @ Hitch; lbs. (kg.) Lift Cap. @ 24" Behind Ball Ends; lbs. (kg.) | 1 Position / Response None Adjustable Rod 1,210 (550) 694 (315) |
| HYDRAULICS | Total Pump Flow; gpm (lpm) Flow @ Remotes; gpm (lpm) Operating Pressure; PSI (BAR) Remotes | 7.9 (30) 5.3 (20) 1,990 (137) Optional |
| POWER STEERING | | Hydrostatic |
| BRAKES & FINAL DRIVES | Differential Lock (Type) Control | Mechanical Pedal |
| FOUR-WHEEL-DRIVE FRONT AXLE | Controls Method of Engagement Shaft Shield Open Axle Shaft Joints | Mechanical Lever Yes None |
| OPERATOR AREA | Chassis Type (Straddle mount or platform) Type of Op Area (ROPS or ROPS cab) Steering Wheel Adjustment (tilt/telescope) Transmission Control Location Seat (Spring Cushion or Spring Suspended) | Semi - Flat Platform Fixed ROPS Fixed Left Console Spring Cushion |
| 4WD DIMENSIONS & WEIGHTS (with R1 agricultural tires) | Wheelbase; in. (mm) Overall Length; in. (mm) Min Overall Width; in. (mm) Height to Top of ROPS; in. (mm) Tire Size - Front Treadwidth - Front; in. (mm) Tire Size - Rear Treadwidth Rear; in. (mm) Clearance Under Axle; in. (mm) Turn Radius w/o Brakes; 4WD engaged; ft. (m) Turn Radius w/Brakes; 4WD engaged; ft. (m) Shipping Weight; lbs. (kg) | 59.9 (1,521) 105.5 (2,680) 41.0 (1,041) 75.2 (1,910) 5.00 - 12 29.5 (749) 9.5 - 15 31.5 - 36.2 (800-919) 11.0 (279) 8.0 (2.7) NA 1,499 (680) |
| CAPACITIES | Fuel tank; gal. (L) | 6.0 (23) |