

EHB 11 S magic Electric Drilling/Chisseling Hammer, 115V, spline dri

Item Number: 0007096

EHB 11 S magic

Light and powerful!

>> Maximum work output is easy with the EHB as this high performance, lightweight electric rotary/demolition hammer is ideal for a wide range of applications. Designed for building remodeling, heating, sanitary, plumbing or scaffolding applications as well as demolition jobs. The optimum weight distribution allows the EHB to be easily operated in an overhead position. <<



Additional Advantages

- With spline (S) tool holder.
- Tough, powerful three-phase motor. No rotor windings, so no break-downs, no downtimes - simply magic.
- Contactless speed adjustment. Completely wear-free - simply magic.
- No carbon brushes. No workshop maintenance. No O-rings, just regrease on site - simply magic.
- New high-tech percussion system. Concentrated, even performance on both hard and soft material.
- Pro-Ergo
- ®
- -Grip System. For fast, easy change of grip during operation. Handle positions can be individually adjusted. The "magic" is easy to hold, allowing you to work more efficiently. Substantially more performance in the same working time - simply magic.
- Inverter integrated into the hammer - unique worldwide. Automatic voltage compensator provides protection against power peaks/drops in mains supply. Makes working safe - simply magic.

- Injection-moulded carrycase for handy storage, together with tools. Easy to transport, well-protected and stackable - simply magic.
- The "magic" is a powerful and durable solution. High performance designed for long-term use. No more downtimes caused by burnt-out rotor windings, for example, which can strain both your nerves and your wallet. Seen over their entire service life, reliable machines cost less.



Description	Metric	Imperial
L x w x h (without tool)	620 x 105 x 245 mm	24.4 x 4.1 x 9.6 in
Weight without tool	11,7 kg	25.4 lb
Shank	spline drive mm	spline drive in
Percussion rate (adjustable)	1.300 - 2.150 1/min	1,300 - 2,150 blows/min
Drill speed	140-225 1/min	140-225 rpm
Single stroke impact	19 (1,9) J (mkp)	14 ft lb/blow
Demolition performance	600 kg/h	1,320 lb/h
Drive engine	three-phase induction motor with inverter in series for alternating current 50/60 Hz with protective insulation	
Voltage	110 - 127 1~ V	110 - 127 1~ V
Rated current	13 A	13 A
Power draw (required generator output: 3,3 kW)	1,2 kW	1.6 hp
Percussion system	air-cushioned percussion system	
Drilling drive	with safety clutch and disconnectable drive shaft	
Sound power level conforming to EC guideline 84/537/EEC		

Standard Package - EHB 11 S magic

includes 4 m power cable, additional handle, grease cartridge, injection-moulded carrycase with tool compartments, operator's manual and parts book

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Monday, March 1, 2010

