


SPECIFICATIONS

MODEL		B21	
Engine	Gross power (SAE)	HP (kW)	21.0 (15.7)
	Net power (SAE)	HP (kW)	19.0 (14.2)
	Total displacement	cu. in. (cm ³)	61.1 cu. in. (1001)
	No. of cylinders		3
	Rated speeds		2600 rpm
Transmission/Drive Train	Type		HST (3 Range)
	No. of speeds		Infinite
	Clutch		Dry, Single
	Power Steering		Integral
	Max. traveling speed	mph (km/h)	11.1 (17.8)
	Shift lever position		Seat side, right
PTO System	Max PTO Power	HP (kW)	13.5 (10.0)
	Rear PTO		540 rpm, Live-continuous running
Hydraulic System	Type		Open center/constant flow
	Pump capacity	gpm. (l/min)	8.5 (32)
	Maximum Operating Pressure		2000
	3-Point Hitch Type		Category I
	3-Point Hitch lift capacity at 24 in. (610 mm) behind LP	lbs. (kg)	1057 (479)
	Position control		Standard
Dimensions & Weight	Fuel Tank Capacity	gal. (l)	6.3 (24)
	Wheel Base	in. (mm)	60.4 (1535)
	Front Tread	in. (mm)	37.8 (960)
	Rear Tread	in. (mm)	41.3 (1050)
	Weight with Loader, Backhoe and ROPS/FOPS	lbs. (kg)	3836 (1740)
	Min. Turning Radius w/o brake	ft. (m)	9.4 (2.85)
ROPS/FOPS			4 Post, with retractable seat belt
Tire Size	Front		23X8.50-14 R4 (IND)
	Rear		12.4-16 R4 (IND)
Other Performance Features	Hood		Slanted hard nose hood
	Frame		Loader-integrated reinforced frame
	Brakes		Wet Disc Brakes
	Seat		Movable seat (Reinforced type)
	Steering Wheel		Tilt steering wheel
	Muffler		Muffler enclosed (w/spark arrestor)
	Pedals		Hanging type pedals
	Deck		Full-floating ISO-mounted Flat deck

All standard equipment in base model machines except where noted.

The company reserves the right to change the above specifications without notice.

These Specifications are for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.